

JOINT COMPOUND SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name:	JOINT COMPOUND
Product Use:	All-purpose drying-type compounds used for finishing gypsum board products. Use per manufacturer's recommendations
Company:	Stella Sealants Corporation
Address:	6915 15th street east, ste 201 Sarasota, FL 34243, USA
Website:	www.stellasealants.com
Email:	info@stellasealants.com
Telephone:	+1(941)357-1566
Fax:	+1(941)359-1630
24 Hour Emergency Number	(844)200-1672

Product Identifiers

Easy Finish Topping	ProForm All Purpose Machine Grade
Easy Finish All Purpose	ProForm Lite
ProForm All Purpose Heavy Viscosity	ProForm Lite with Dust-Tech
ProForm All Purpose Export EX 70	ProForm Ultra Lite All Purpose
ProForm Multi-Use	ProForm Topping
ProForm Taping	ProForm XP with Dust-Tech
ProForm Taping Lite	ProForm XP Lite with Dust-Tech
ProForm Lite Blue	Advantage
ProForm Texture Grade	Advantage Lite
ProForm Tinted Lite	Advantage Topping
ProForm Pre-Blend 50 lb. bag	ProForm Concrete-Cover Compound
ProForm All Purpose	ProForm Factory Built Housing Texture Grade Compound

Section 2. Hazards Identification

United States (US)

According to OSHA 29CFR 1910.1200 (HCS)

GHS Classification of the substance or mixture

Carcinogenicity - Category 1A - (H-350)

Specific target organ toxicity, repeated exposure – Category 1 (H-372)

Acute toxicity, inhalation - Category 4 (H-332)

Skin corrosion/irritation Category 2 (H315)

GHS Label Elements

Pictogram



Signal Word

Danger

JOINT COMPOUND SAFETY DATA SHEET

Hazard Statements

- H-350 May cause cancer.
H-332, 372 Harmful if inhaled. Causes damage to organs (lungs) through prolonged or repeated exposure.
H-315 Causes skin corrosion/irritation

Precautionary Statements

Prevention

- Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust.
Use personal protective equipment as required. (See Section 8)
Use engineering controls and wet methods to minimize dust.

Response

- If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
If on skin, wash with plenty of soap and water.
If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Get medical attention if exposed or concerned.

Storage

Store material in a cool, dry, ventilated area, away from excessive heat or sunlight.

Disposal

Dispose of material in accordance with federal, state, and local regulations

Section 3. Composition/Information on Ingredients

HAZARDOUS SUBSTANCES

Chemical Name	Common name/ Synonym	Identifiers CAS Number	% (weight)
Calcium Carbonate or Calcium/ Magnesium Carbonate	Limestone or Dolomite	1317-65-3 16389-88-1	<50
And may contain one or more of the following:			
Mixture-silicates and aluminates	Mica	12001-26-2	<10
Hydrated magnesium silicate	Talc (non-asbestiform)	14807-96-6	<5
Mixture-various metal oxides	Perlite	93763-70-3	<10
magnesium aluminum phyllosilicate	Attapulgite Clay	12174-11-7	<5
Magnesium silicate	Sepiolite Clay	63800-37-3	<5
Magnesium aluminum phyllosilicate	Smectite Clay	1302-78-9	<5
Polyvinyl Acetate Latex		9003-20-7	<5
Ethylene Vinyl Acetate Latex		24937-78-8	<5
Vinyl Acetate/Acrylic Copolymer		108-05-4	<5

JOINT COMPOUND SAFETY DATA SHEET

Raw materials in this product contain respirable crystalline silica as an impurity. The OSHA PEL respirable crystalline silica has been lowered to 0.05 mg/m³, effective June 23, 2016 with compliance dates of September 23, 2017 for construction and June 23, 2018 for general industry. Testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL. Because every jobsite is different, NGC cannot provide customers with any documentation that would exempt a customer from OSHA investigating the customer's jobsite for respirable silica. Actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.

Section 4. First Aid Measures

Skin Contact:	Flush and wash skin with soap and water. Utilize lotions to alleviate dryness if present. Seek medical attention if irritation persists.
Eye Contact:	Do not rub or scratch eyes. Immediately flush eyes with water for 15 minutes. Remove contact lenses (if applicable). Seek medical attention if irritation persists.
Inhalation:	Remove exposed individual to fresh air immediately. If breathing difficulty persists, seek medical attention.
Ingestion:	This product is not expected to be hazardous and no harmful effects are expected upon ingestion of small amounts. Larger amounts may cause abdominal discomfort or possible obstruction of the digestive tract. Seek medical attention if problems persist.

Medical Conditions aggravated by exposure

Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma.
Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.

Section 5. Firefighting Measures

Extinguishing Media

Dry chemical, foam, water, or extinguishing media appropriate for surrounding fire.

Unusual Fire and Explosion Hazards

Mixture poses no fire-related hazard.

Special hazards arising from the mixture

None known

Special Protective Equipment and Precautions for Firefighters

A SCBA is recommended to limit exposures to combustion products when fighting any fire.

JOINT COMPOUND SAFETY DATA SHEET

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

No special precautions required.

General recommendations:

Wear appropriate Personal Protective Equipment. (See Section 8)

Maintain proper ventilation.

Environmental precautions

This product does not present an ecological hazard to the environment.

Dispose of in accordance with applicable federal, state, and local regulations.

Methods and materials for containment and cleaning up

Shovel or scoop spilled material back into container for use, if possible, or disposal.

Maintain proper ventilation to minimize dust.

Avoid washing material down drains. This material will eventually set and can cause clogs.

Section 7. Handling and Storage

Precautions for safe handling

Avoid breathing vapors when opening container.

Avoid breathing dust.

Minimize generation of dust.

Provide appropriate exhaust ventilation at places where dust is formed.

Avoid contact with eyes, skin and clothing.

Wear recommended personal protective equipment when handling. (See Section 8)

Conditions for safe storage, including any incompatibilities

Store material in a cool, dry, ventilated area, away from excessive heat or sunlight.

Keep from freezing to preserve usefulness.

Keep containers closed when not in use.

Avoid contact with strong acids.

Section 8. Exposure Control/Personal Protection

Control Parameters

Exposure Limits

Component	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Calcium Carbonate or Dolomite (limestone)	15 (T) 5 (R)	10 (T)
Mica	20 mppcf	3
Talc (non-asbestiform)	20 mppcf	2
Perlite	15 (T) 5 (R)	10 (T)
Attapulgate Clay	15 (T) 5 (R)	10 (T)

JOINT COMPOUND SAFETY DATA SHEET

Sepiolite Clay	15 (T) 5 (R)	10 (T)
Smectite Clay	15 (T) 5 (R)	10 (T)
Crystalline Silica ¹	[(10) / (%SiO ₂ +2)] (R); [(30) / (%SiO ₂ +2)] (T)	0.025(R)
Polyvinyl Acetate Latex	NE	NE
Ethylene Vinyl Acetate Latex	NE	NE

1 – Present as an impurity in raw materials

T- Total Dust

R- Respirable Dust

NE- None Established

Mppcf – million particles per cubic foot

Exposure Controls

Appropriate Engineering Controls

Work/Hygiene Practices: Utilize methods to minimize dust production. Use sanders equipped with vacuum capabilities whenever possible. Utilize a light water spray when feasible.

Ventilation: Provide local and general exhaust ventilation sufficient to maintain a dust level below the PEL/TLV.

Personal Protective Equipment

Respiratory Protection

A NIOSH approved particulate respirator is recommended in poorly ventilated areas or if the PEL/TLV is exceeded. OSHA's 29 CFR 1910.134 (Respiratory Protection Standard) must be followed whenever work conditions require respirator use.

Eye Protection

Safety glasses or goggles.

Skin

Gloves, protective clothing and/or barrier creams may be utilized if conditions warrant.

Section 9. Physical and Chemical Properties

- (a) Appearance: A white to gray paste
- (b) Odor: Mild latex initially, Low to none after opening
- (c) Odor threshold: Not available
- (d) pH : 7-9
- (e) Melting point/freezing point: Not Available
- (f) Initial boiling point and boiling range: Not Available
- (g) Flash point: Not available
- (h) Evaporation rate: Not available
- (i) Flammability (solid, gas): Not flammable
- (j) Upper/lower flammability or explosive limits: Not available

JOINT COMPOUND SAFETY DATA SHEET

- (k) Vapor pressure: Not available
- (l) Vapor density: Not available
- (m) Relative density: ~1.0-1.8
- (n) Solubility(ies): slightly soluble in water
- (o) Partition coefficient: n-octanol/water: Not available
- (p) Auto-ignition temperature: Not available
- (q) Decomposition temperature: 825oC
- (r) Viscosity: Not available
- (s) Volatile organic compound (VOC) content: <2 g/l

Section 10. Stability and Reactivity

- (b) Chemical stability: Stable in dry environments
- (c) Possibility of hazardous reactions: None known
- (d) Conditions to avoid (e.g., static discharge, shock, or vibration): None known
- (e) Incompatible materials: Strong acids
- (f) Hazardous decomposition products: None known. Above 825o C limestone (CaCO₃) decomposes to calcium oxide (CaO) and carbon dioxide.(CO₂)

Section 11. Toxicological Information

Information on Toxicological effects

Information on likely routes of exposure

Ingestion: Possible abdominal obstruction.

Inhalation: Dust may irritate respiratory system. Chronic exposure may result in lung disease. (See below)

Skin contact: May cause irritation, rash, itching, or dermatitis.

Eye contact: Dust may cause mechanical irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Acute exposure to airborne dust concentrations in excess of the PEL/TLV may result in coughing, dyspnea, wheezing, and a burning irritation of the nose, throat, and upper respiratory tract, along with possible impaired pulmonary function. Chronic exposures may result in lung disease. (Silicosis and/or lung cancer)

Toxicological data

No toxicological data is available for this product. Toxicological information for components of this product listed below.

Acute toxicity: Not available

Skin corrosion/irritation: Not available

Serious eye damage/eye irritation: Not available

Skin sensitization: Not available

Respiratory sensitization: Not available

Sensitization: Not available

Mutagenicity: Not available

Carcinogenicity: Not available

JOINT COMPOUND SAFETY DATA SHEET

This product contains crystalline silica (quartz) as a naturally occurring impurity in some of the raw materials. The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen.

Some products may contain attapulgite clay. IARC classifies attapulgite (long fiber) carcinogenic to humans, Group 2B. Attapulgite is not classified as a carcinogen by NTP or OSHA.

Exposures to respirable crystalline silica are not expected during the recommended use of this product. However, actual levels must be determined by workplace Industrial Hygiene testing.

Reproductive effects: Not available

Specific target organ toxicity –

single exposure: Not available

Aspiration toxicity: Not available

Section 12. Ecological Information

(a) Ecotoxicity (aquatic and terrestrial, where available): This product does not present an ecological hazard to the environment.

(b) Persistence and degradability: Unknown

(c) Bioaccumulative potential: Limestone is a naturally occurring mineral. Biodegradation and/or bioaccumulation potential is not applicable.

(d) Mobility in soil: Unknown

(e) Other adverse effects (such as hazardous to the ozone layer): None known

JOINT COMPOUND SAFETY DATA SHEET

Section 13. Disposal Considerations

This material is not considered a hazardous waste. Dispose of according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14. Transport Information

This product is not a DOT hazardous material
Shipping Name: Same as product name
ICAO/IATA/IMO: Not applicable

Section 15. Regulatory Information

All ingredients are included on the TSCA inventory.

Federal Regulations

SARA Title III: Not listed under Sections 302, 304, and 313

CERCLA: Not listed

RCRA: Not listed

OSHA: Dust and potential respirable crystalline silica generated during product use may be hazardous.

State Regulations

California Prop 65: Respirable crystalline silica is known to the state of California to cause cancer. Industrial hygiene monitoring during recommended use of this product failed to identify any respirable crystalline silica.

Canada WHMIS

All components of this product are included in the Canadian Domestic Substances List (DSL).

Crystalline silica: WHMIS Classification D2A

JOINT COMPOUND SAFETY DATA SHEET

Section 16. Other Information

Key to Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Services Number
CFR	Code of Federal Regulations
DOT	Department of Transportation
EPA	Environmental Protection Agency
HEPA	High Efficiency Particulate Air
HCS	Hazard Communications Standard
HMIS	Hazardous Material Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMO	International Maritime Organization
NIOSH	National Institute for Occupational Safety and Health
NFPA	National Fire Protection Association
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
PPE	Personal Protective Equipment
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein. This safety data sheet was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material, or the results to be obtained for the use thereof.

Issue date: March 03, 2015

Revision: June 15, 2017