

ULTRA DRY 70 STONE SEALER

SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name: ULTRA DRY 70 STONE SEALER
Product Use: Masonry and stone water repellent
Company: Stella Sealants Corporation
Address: 6915 15th street east, ste 201
Sarasota, FL 34243, USA
Website: www.stellasealants.com
Email: info@stellasealants.com
Telephone: +1(941)357-1566
Fax: +1(941)359-1630
24 Hour Emergency Number: (844)200-1672
Transportation emergency: (CHEMTREC, USA) (800)424-9300

Section 2. Hazards Identification

Classification Symbol(s) of Product

Not a hazardous substance or mixture per 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200.

Signal Word No Signal Word has been assigned.

Section 3. Hazardous Composition/Information on Ingredients

HAZARDOUS SUBSTANCES

Chemical Name	CAS No.	Wt.% Range	GHS Symbols	GHS Statements
---------------	---------	------------	-------------	----------------

No hazardous items exist

Section 4. First Aid Measures

Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

Ingestion: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

ULTRA DRY 70 STONE SEALER

SAFETY DATA SHEET

Section 5. Firefighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

No unusual fire or explosion hazards noted. Keep containers tightly closed.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam.

If water is used, fog nozzles are preferred.

Section 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispose of according to local, state, and federal regulations.

Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent.

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Section 7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Avoid contact with eyes.

Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Keep from freezing. Keep container closed when not in use. Store in a dry, well ventilated place.

Keep container tightly closed when not in use.

Section 8. Exposure Control/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLVTWA	ACGIH TLVSTEL	OSHA PEL-TWA	OSHA PELCEILING
---------------	---------	--------------------	--------------	---------------	--------------	-----------------

No hazardous items exist

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

ULTRA DRY 70 STONE SEALER

SAFETY DATA SHEET

Section 9. Physical and Chemical Properties

Appearance:	Liquid
Physical State:	Liquid
Odor:	Mild Chemical
VOC (grams/liter)	5.63
Relative Density:	1.0-1.05
pH:	7.0-9.0
Freeze Point, °C:	0
Viscosity:	N.D.
Solubility in Water:	Miscible
Partition Coefficient, n-octanol/ water:	N.D.
Decomposition Temp., °C:	N.D.
Boiling Range, °C:	100
Explosive Limits, vol%:	N.A. - N.A.
Flammability:	Does not Support Combustion
Flash Point, °C:	N.D.
Evaporation Rate:	Slower than Ether
Auto-ignition Temp., °C:	N.D.
Vapor Density:	Heavier than Air
Vapor Pressure:	N.D.

Section 10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

Section 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: Low hazard for usual industrial handling or commercial handling by trained personnel. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

ACUTE TOXICITY VALUES

ULTRA DRY 70 STONE SEALER

SAFETY DATA SHEET

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
No hazardous items exist				
N.I. - No Information				

Section 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

Section 13. Disposal Considerations

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

Section 14. Transport Information

	Domestic (USDOT)	International (IMDG)	Air (IATA)	TDG (Canada)
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

Section 15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

No Information

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

ULTRA DRY 70 STONE SEALER

SAFETY DATA SHEET

Section 16. Other Information

HMIS RATINGS

Health:	1	Flammability:	1
Physical Hazard:	0	Personal Protection:	X

NFPA RATINGS

Health:	1	Flammability:	1
Instability	0		

VOLATILE ORGANIC COMPOUNDS, (VOC) Grams per Liter: 5.63 / 0.05 pounds/Gallon

SDS REVISION DATE: 1/23/2018

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Stella Sealants Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet.

However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials.

Stella Sealants Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use.

All materials may present unknown hazards and should be used with caution.

The information and recommendations in this material safety data sheet are offered for the users' consideration and examination.

It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Issue date: July 01, 2017

Revision: January 23, 2018